



WideMAXX® Suspension Kit

Tip: Refer to the exploded views included with your truck to assist with installation of the Wide Maxx® Suspension Kit.

Suspension Tuning

1. Remove the two front and two rear shocks from the truck.
2. Remove the shock springs from all four shocks. Install the rear shock springs on the front shocks. **The front springs are not used with the Wide Maxx suspension.**
3. Install the new shock springs (included) on the rear shocks.
4. For optimal suspension performance, replace the 30wt silicone shock oil in the rear shocks with 50wt silicone shock oil (part #5034, sold separately). Be sure to fill the shocks with 100% pure silicone shock oil to help prolong the life of the seals. When adding shock oil, be sure to allow any air bubbles to escape. **Note: The rear shocks use the 1.2mm shock piston.**
5. Reinstall the front and rear shocks on the truck.

If you have questions or need technical assistance, call Traxxas at

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

Replacement Parts

- | | | | |
|-------|---|-------|--|
| 8958 | Rod ends (4) (assembled with steel pivot balls) (replacement ends for #8547A, 8547R, 8547X, 8948A, 8948G, 8948R, 8948X, 8997A, 8997G, 8997R, 8997X) | 8997R | Toe links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8969 | Springs, shock (natural finish) (GT-Maxx®) (1.725 rate) (2) | 8997X | Toe links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8993 | Half shaft set, left or right (plastic parts only) (internal splined half shaft/ external splined half shaft) (4 assemblies) (for use with #8995 WideMaxx® suspension kit) | 8998 | Suspension arms, upper, black (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8993A | Half shafts, outer (extended, front or rear) (4)/ e-clips (8) (for use with #8995 WideMaxx® suspension kit) | 8998A | Suspension arms, upper, white (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8994 | Stub axle assembly, outer (front or rear) (assembled with internal-splined half shaft) (for use with #8995 WideMaxx® suspension kit) | 8998G | Suspension arms, upper, green (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996 | Driveshaft assembly, front or rear, Maxx® Duty (1) (left or right) (fully assembled, ready to install)/ screw pin (1) (for use with #8995 WideMaxx® suspension kit) | 8998R | Suspension arms, upper, red (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996A | Driveshaft, steel constant-velocity (shaft only, 109.5mm) (4) (for conversion of #8950X driveshafts to WideMaxx® suspension) | 8998T | Suspension arms, upper, orange (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996R | Driveshaft, steel constant velocity (shaft only, 109.5mm) (1) (replacement shaft for #8996X) | 8998X | Suspension arms, upper, blue (left or right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8996X | Driveshafts, steel constant-velocity (assembled), front or rear (4) (for use with #8995 WideMaxx® suspension kit) (requires #8654 series 17mm splined wheel hubs and #7758 series 17mm nuts for a complete set) | 8999 | Suspension arms, lower, black (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8997 | Toe links, 119.8mm (108.6mm center to center) (black) (2) (for use with #8995 WideMaxx® suspension kit) | 8999A | Suspension arms, lower, white (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8997A | Toe links, front (TUBES orange-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) | 8999G | Suspension arms, lower, green (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| 8997G | Toe links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (2) (for use with #8995 WideMaxx® suspension kit) | 8999R | Suspension arms, lower, red (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| | | 8999T | Suspension arms, lower, orange (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |
| | | 8999X | Suspension arms, lower, blue (left and right, front or rear) (2) (for use with #8995 WideMaxx® suspension kit) |

Covers Part #8995, 8995A, 8995G, 8995R, 8995T, 8995X

